



Двигатели для генераторов и мотопомп серии VANGUARD

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72,
Астана+7(7172)727-132,
Белгород(4722)40-23-64,
Брянск(4832)59-03-52,
Владивосток(423)249-28-31,
Волгоград(844)278-03-48,
Вологда(8172)26-41-59,
Воронеж(473)204-51-73,
Екатеринбург(343)384-55-89,
Иваново(4932)77-34-06,
Ижевск(3412)26-03-58,
Казань(843)206-01-48,
Калининград(4012)72-03-81,
Калуга(4842)92-23-67,
Кемерово(3842)65-04-62,
Киров(8332)68-02-04,

Краснодар(861)203-40-90,
Красноярск(391)204-63-61,
Курск(4712)77-13-04,
Липецк(4742)52-20-81,
Магнитогорск(3519)55-03-13,
Москва(495)268-04-70,
Мурманск(8152)59-64-93,
Набережные Челны(8552)20-53-41,
Нижний Новгород(831)429-08-12,
Новокузнецк(3843)20-46-81,
Новосибирск(383)227-86-73,
Орел(4862)44-53-42,
Оренбург(3532)37-68-04,
Пенза(8412)22-31-16,
Пермь(342)205-81-47,
Ростов-на-Дону(863)308-18-15,

Рязань(4912)46-61-64,
Самара(846)206-03-16,
Санкт-Петербург(812)309-46-40,
Саратов(845)249-38-78,
Смоленск(4812)29-41-54,
Сочи(862)225-72-31,
Ставрополь(8652)20-65-13,
Тверь(4822)63-31-35,
Томск(3822)98-41-53,
Тула(4872)74-02-29,
Тюмень(3452)66-21-18,
Ульяновск(8422)24-23-59,
Уфа(347)229-48-12,
Челябинск(351)202-03-61,
Череповец(8202)49-02-64,
Ярославль(4852)69-52-93

3
YEAR
COMMERCIAL
LIMITED
WARRANTY



Briggs & Stratton, the manufacturer of small, commercial grade 4-stroke petrol engines, offers a 3-Year Limited Global Warranty for a full horsepower range of horizontal and vertical shaft air-cooled engines.

VANGUARD™

HORIZONTAL

VANGUARD™ 5,5 - 6,5 GROSS HP*



Engine type

Single cylinder, 4-stroke,
air-cooled, OHV

Model Number

13H1 **13H3**

Gross Power (HP[kW])
@ 3'600 rpm

5,5* **6,5***
[4,1] **[4,8]**

Displacement (cc)

205

Cylinder

Cast Iron Sleeve

Bore & Stroke (mm)

68,3 x 55,8

Fuel tank capacity (l)

3,8

Oil capacity (l)

0,6

Dry weight (kg)

18,7

Dimensions
L x W x H (mm)

275 x 391 x 363

Features

TransportGuard™

Optional

Electric Start

Cover options

NA

Fuel Consumption in Litres per Hour**

Full Load: 13H1 13H3

Litres: 2,02 2,36

* All power levels are stated gross horsepower per SAE J1940 as rated by Briggs & Stratton.

** (Load @ 3'600 rpm). Fuel consumption is depending on engine configuration, application and operating conditions.

HORIZONTAL VANGUARD™ 8 - 10 GROSS HP*



ENTRY

STANDARD

PERFORMANCE

PREMIUM

COMMERCIAL

Engine type	Single cylinder, 4-stroke, air-cooled, OHV	
Model Number	19H1	19H2
Gross Power (HP[kw]) @ 3'600 rpm	8,0* [5,9]	10,0* [7,5]
Displacement (cc)	305	
Cylinder	<i>Cast Iron Sleeve</i>	
Bore & Stroke (mm)	79,2 x 61,9	
Fuel tank capacity (l)	4,1	
Oil capacity (l)	0,8	
Dry weight (kg)	25,9	
Dimensions L x W x H (mm)	318 x 421 x 406	
Features	TransportGuard™	
Optional	Electric Start	
Cover options	NA	

Fuel Consumption in Litres per Hour**

Full Load: 19H1 19H2

Litres: 2,91 3,30

* All power levels are stated gross horsepower per SAE J1940 as rated by Briggs & Stratton.

** (Load @ 3'600 rpm). Fuel consumption is depending on engine configuration, application and operating conditions.

HORIZONTAL VANGUARD™ 13 GROSS HP*



Engine type	Single cylinder, 4-stroke, air-cooled, OHV
Model Number	2454
Gross Power (HP[kW]) @ 3'600 rpm	13,0* [9,7]
Displacement (cc)	392
Cylinder	Cast Iron Sleeve
Bore & Stroke (mm)	89,0 x 63,0
Fuel tank capacity (l)	7,1
Oil capacity (l)	1,4
Dry weight (kg)	33,2
Dimensions L x W x H (mm)	398 x 463 x 466
Features	-
Optional	Electric Start
Cover options	NA

Fuel Consumption in Litres per Hour**

Load: Full

Litres: 4,6

* All power levels are stated gross horsepower per SAE J1940 as rated by Briggs & Stratton.

** (Load @ 3'600 rpm). Fuel consumption is depending on engine configuration, application and operating conditions.

HORIZONTAL VANGUARD™ 14 - 16 GROSS HP*



Engine type	V-Twin, 4-stroke, air-cooled, OHV
Model Number	2954 3054

Gross Power (HP[kW]) @ 3'600 rpm	14,0* 16,0* [10,4] [11,9]
Displacement (cc)	479
Cylinder	Cast Iron Sleeve
Bore & Stroke (mm)	68,0 x 66,0
Fuel tank capacity (l)	NA
Oil capacity (l)	1,7
Dry weight (kg)	32,7
Dimensions L x W x H (mm)	279 x 410 x 438
Features	Full Pressure Lubrication, Oil Filter
Optional	Rewind Start, Muffler, Fuel Tank
Cover options	NA

Fuel Consumption in Litres per Hour**
Load: Full

Litres: 4,2

* All power levels are stated gross horsepower per SAE J1940 as rated by Briggs & Stratton.
** (Load @ 3'600 rpm). Fuel consumption is depending on engine configuration, application and operating conditions.

HORIZONTAL VANGUARD™ 18 GROSS HP*



Engine type

V-Twin, 4-stroke,
air-cooled, OHV

Model Number

3564

Gross Power (HP[kW])
@ 3'600 rpm

18,0*
[13,4]

Displacement (cc)

570

Cylinder

Cast Iron Sleeve

Bore & Stroke (mm)

72,0 x 70,0

Fuel tank capacity (l)

NA

Oil capacity (l)

1,7

Dry weight (kg)

33,6

Dimensions
L x W x H (mm)

318 x 410 x 438

Features

Full Pressure Lubrication, Oil Filter

Optional

Rewind Start, Muffler, Fuel Tank,
Cyclonic Air Filter

Cover options

NA

Fuel Consumption in Litres per Hour**

Load: Full

Litres: 6,2

* All power levels are stated gross horsepower per SAE J1940 as rated by Briggs & Stratton.

** (Load @ 3'600 rpm). Fuel consumption is depending on engine configuration, application and operating conditions.

HORIZONTAL VANGUARD™ 21 - 23 GROSS HP*



Engine type	V-Twin, 4-stroke, air-cooled, OHV
Model Number	3854 3864
Gross Power (HP[kW]) @ 3'600 rpm	21,0* 23,0* [15,7] [17,2]
Displacement (cc)	627
Cylinder	Cast Iron Sleeve
Bore & Stroke (mm)	75,5 x 70,0
Fuel tank capacity (l)	NA
Oil capacity (l)	1,7
Dry weight (kg)	35
Dimensions L x W x H (mm)	318 x 407 x 449
Features	Full Pressure Lubrication, Oil Filter
Optional	Rewind Start, Muffler, Cyclonic Air Cleaner
Cover options	NA

Fuel Consumption in Litres per Hour**
Load: Full

Litres: 6,9

* All power levels are stated gross horsepower per SAE J1940 as rated by Briggs & Stratton.
** (Load @ 3'600 rpm). Fuel consumption is depending on engine configuration, application and operating conditions.

HORIZONTAL

VANGUARD™ 25 - 31 GROSS HP*



Engine type

V-Twin, 4-stroke,
air-cooled, OHV

Model Number

5404 5414 5424 **5434**

Gross Power (HP[kW])
@ 3'600 rpm

25,0* 27,0* 29,0* **31,0***
[18,6] [20,1] [21,6] **[23,1]**

Displacement (cc)

896

Cylinder

Cast Iron Sleeve

Bore & Stroke (mm)

85,5 x 78,0

Fuel tank capacity (l)

NA

Oil capacity (l)

2,3

Dry weight (kg)

56,8

Dimensions
L x W x H (mm)

379 x 496 x 725

Features

Full Pressure Lubrication, Oil Filter

Optional

Muffler, Flat Panel Air Cleaner

Cover options

NA

Fuel Consumption in Litres per Hour**

Load: Full

Litres: 8,0

* All power levels are stated gross horsepower per SAE J1940 as rated by Briggs & Stratton.

** (Load @ 3'600 rpm). Fuel consumption is depending on engine configuration, application and operating conditions.

HORIZONTAL VANGUARD™ 33 - 35 GROSS HP*



Engine type	V-Twin, 4-stroke, air-cooled, OHV
Model Number	6114 6134
Gross Power (HP[kW]) @ 3'600 rpm	33,0* 35,0* [24,6] [26,1]
Displacement (cc)	993
Cylinder	Cast Iron Sleeve
Bore & Stroke (mm)	85,5 x 86,5
Fuel tank capacity (l)	NA
Oil capacity (l)	2,3
Dry weight (kg)	56,8
Dimensions L x W x H (mm)	379 x 496 x 725
Features	Full Pressure Lubrication, Oil Filter
Optional	Muffler, Flat Panel Air Cleaner
Cover options	NA

Fuel Consumption in Litres per Hour**
Load: Full

Litres: 8,0

* All power levels are stated gross horsepower per SAE J1940 as rated by Briggs & Stratton.
** (Load @ 3'600 rpm). Fuel consumption is depending on engine configuration, application and operating conditions.

HORIZONTAL VANGUARD™ 23,6 GROSS HP*



Engine type	3 Cylinder, 4-stroke, Liquid-Cooled Diesel
Model Number	5224 (DM 850D)
Gross Power (HP[kW]) @ 3'600 rpm	23,6* [17,5]
Displacement (cc)	850
Cylinder	Cast Iron Sleeve
Bore & Stroke (mm)	68,0 x 78,0
Fuel tank capacity (l)	NA
Oil capacity (l)	3,0
Dry weight (kg)	84
Dimensions L x W x H (mm)	435 x 443 x 534
Features	-
Optional	Power Unit Assemblies
Cover options	NA

Fuel Consumption in g/kWh**
Load: Full

Gram: 290

* All power levels are stated gross horsepower per SAE J1940 as rated by Briggs & Stratton.
** (Load @ 3'600 rpm). Fuel consumption is depending on engine configuration, application and operating conditions.

HORIZONTAL VANGUARD™ 26,5 GROSS HP*



Engine type	3 Cylinder, 4-stroke, Liquid-Cooled Diesel
Model Number	5824 (DM 950D)
Gross Power (HP[kW]) @ 3'600 rpm	26,5* [19,7]
Displacement (cc)	952
Cylinder	Cast Iron Sleeve
Bore & Stroke (mm)	72,0 x 78,0
Fuel tank capacity (l)	NA
Oil capacity (l)	3,0
Dry weight (kg)	89
Dimensions L x W x H (mm)	435 x 443 x 534
Features	-
Optional	Power Unit Assemblies
Cover options	NA

Fuel Consumption in g/kWh**
Load: Full

Gram: 290

* All power levels are stated gross horsepower per SAE J1940 as rated by Briggs & Stratton.
** (Load @ 3'600 rpm). Fuel consumption is depending on engine configuration, application and operating conditions.

HORIZONTAL

VANGUARD™ 31 - 34 GROSS HP*



Engine type	3 Cylinder, 4-stroke, Liquid-Cooled, Turbo Diesel	
Model Number	5884 (DM 950DT)	58A4 (DM 954DT)
Gross Power (HP[kW]) @ 3'600 rpm	31,0* [23,1]	34,0* [25,3]
Displacement (cc)	952	
Cylinder	Cast Iron Sleeve	
Bore & Stroke (mm)	72,0 x 78,0	
Fuel tank capacity (l)	NA	
Oil capacity (l)	3,0	
Dry weight (kg)	89	
Dimensions L x W x H (mm)	434 x 448 x 559	
Features	-	
Optional	Power Unit Assemblies	
Cover options	NA	

Fuel Consumption in g/kWh**

Load: Full

Gram: 290

* All power levels are stated gross horsepower per SAE J1940 as rated by Briggs & Stratton.

** (Load @ 3'600 rpm). Fuel consumption is depending on engine configuration, application and operating conditions.



По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72,
Астана+7(7172)727-132,
Белгород(4722)40-23-64,
Брянск(4832)59-03-52,
Владивосток(423)249-28-31,
Волгоград(844)278-03-48,
Вологда(8172)26-41-59,
Воронеж(473)204-51-73,
Екатеринбург(343)384-55-89,
Иваново(4932)77-34-06,
Ижевск(3412)26-03-58,
Казань(843)206-01-48,
Калининград(4012)72-03-81,
Калуга(4842)92-23-67,
Кемерово(3842)65-04-62,
Киров(8332)68-02-04,

Краснодар(861)203-40-90,
Красноярск(391)204-63-61,
Курск(4712)77-13-04,
Липецк(4742)52-20-81,
Магнитогорск(3519)55-03-13,
Москва(495)268-04-70,
Мурманск(8152)59-64-93,
Набережные Челны(8552)20-53-41,
Нижний Новгород(831)429-08-12,
Новокузнецк(3843)20-46-81,
Новосибирск(383)227-86-73,
Орел(4862)44-53-42,
Оренбург(3532)37-68-04,
Пенза(8412)22-31-16,
Пермь(342)205-81-47,
Ростов-на-Дону(863)308-18-15,

Рязань(4912)46-61-64,
Самара(846)206-03-16,
Санкт-Петербург(812)309-46-40,
Саратов(845)249-38-78,
Смоленск(4812)29-41-54,
Сочи(862)225-72-31,
Ставрополь(8652)20-65-13,
Тверь(4822)63-31-35,
Томск(3822)98-41-53,
Тула(4872)74-02-29,
Тюмень(3452)66-21-18,
Ульяновск(8422)24-23-59,
Уфа(347)229-48-12,
Челябинск(351)202-03-61,
Череповец(8202)49-02-64,
Ярославль(4852)69-52-93