



# Снегоуборщики серии В

**По вопросам продаж и поддержки обращайтесь:**

Архангельск (8182)63-90-72,  
Астана+7(7172)727-132,  
Белгород(4722)40-23-64,  
Брянск(4832)59-03-52,  
Владивосток(423)249-28-31,  
Волгоград(844)278-03-48,  
Вологда(8172)26-41-59,  
Воронеж(473)204-51-73,  
Екатеринбург(343)384-55-89,  
Иваново(4932)77-34-06,  
Ижевск(3412)26-03-58,  
Казань(843)206-01-48,  
Калининград(4012)72-03-81,  
Калуга(4842)92-23-67,  
Кемерово(3842)65-04-62,  
Киров(8332)68-02-04,

Краснодар(861)203-40-90,  
Красноярск(391)204-63-61,  
Курск(4712)77-13-04,  
Липецк(4742)52-20-81,  
Магнитогорск(3519)55-03-13,  
Москва(495)268-04-70,  
Мурманск(8152)59-64-93,  
Набережные Челны(8552)20-53-41,  
Нижний Новгород(831)429-08-12,  
Новокузнецк(3843)20-46-81,  
Новосибирск(383)227-86-73,  
Орел(4862)44-53-42,  
Оренбург(3532)37-68-04,  
Пенза(8412)22-31-16,  
Пермь(342)205-81-47,  
Ростов-на-Дону(863)308-18-15,

Рязань(4912)46-61-64,  
Самара(846)206-03-16,  
Санкт-Петербург(812)309-46-40,  
Саратов(845)249-38-78,  
Смоленск(4812)29-41-54,  
Сочи(862)225-72-31,  
Ставрополь(8652)20-65-13,  
Тверь(4822)63-31-35,  
Томск(3822)98-41-53,  
Тула(4872)74-02-29,  
Тюмень(3452)66-21-18,  
Ульяновск(8422)24-23-59,  
Уфа(347)229-48-12,  
Челябинск(351)202-03-61,  
Череповец(8202)49-02-64,  
Ярославль(4852)69-52-93

## BS822E Single Stage - DELUXE Snow Blower



- 22" (55 cm) Clearing Width
- Briggs & Stratton 800 Snow Series™ Engines
- Freeze-Resistant Recoil Starter and Electronic Ignition
- Auger-Assisted Drive System
- Push Button Electric Start
- On-The-Go Chute Rotation
- Quick-Adjust Deflector
- Integrated Headlight

## Specifications

|                           |                                    |
|---------------------------|------------------------------------|
| Stage                     | Single Stage - DELUXE              |
| <b>AUGER / IMPELLER</b>   |                                    |
| Clearing width            | 22" (55 cm)                        |
| Intake height             | 12.5" (32 cm)                      |
| Auger style               | Thermal Plastic Urethane           |
| Auger diameter            | 10" (25.4 cm)                      |
| Impeller diameter         | n/a                                |
| Impeller style            | n/a                                |
| <b>ENGINE</b>             |                                    |
| Engine displacement       | 205 cc                             |
| Engine type               | 4-Cycle - OHV                      |
| Starting system           | Recoil Start + 230V Electric Start |
| Oil                       | 0W30 Synthetic                     |
| <b>CHUTE</b>              |                                    |
| Chute style               | Plastic                            |
| Chute rotation            | 200° Quick Chute                   |
| Chute deflector           | Quick Deflector                    |
| <b>DRIVE SYSTEM</b>       |                                    |
| Drive type                | Auger Propelled                    |
| Number of gears           | n/a                                |
| Tire size                 | 8" x 2" (20 x 5 cm)                |
| Thread                    | n/a                                |
| <b>HANDLES / CONTROLS</b> |                                    |
| Free Hand Control™        | n/a                                |
| Headlight                 | Standard                           |
| Heated hand grips         | n/a                                |
| <b>ACCESSORIES</b>        |                                    |
| Drift cutters             | n/a                                |
| Storage cover             | n/a                                |
| Snow cab                  | n/a                                |

## BL924R Dual Stage - Light Duty Snow Blower



- 24" (61 cm) Clearing Width
- Briggs & Stratton 900 Snow Series™ Engines
- Freeze-Resistant Recoil Starter
- Dual Notched Steel Auger
- Left Side Crank chute control
- Free Hand™ Control
- Rugged Artic Trac™ Tires
- Halogen Headlights

## Specifications

|                           |                                 |
|---------------------------|---------------------------------|
| Stage                     | Dual Stage - Light Duty         |
| <b>AUGER / IMPELLER</b>   |                                 |
| Clearing width            | 24" (61 cm)                     |
| Intake height             | 20" (51 cm)                     |
| Auger style               | Steel - Dual Notched            |
| Auger diameter            | 10" (25.4 cm)                   |
| Impeller diameter         | 10" (25.4 cm)                   |
| Impeller style            | 3 Blades                        |
| <b>ENGINE</b>             |                                 |
| Engine displacement       | 205 cc                          |
| Engine type               | 4-Cycle - OHV                   |
| Starting system           | Recoil Start                    |
| Oil                       | 0W30 Synthetic                  |
| <b>CHUTE</b>              |                                 |
| Chute style               | Steel                           |
| Chute rotation            | Left Side Crank 190° (3.5 Turn) |
| Chute deflector           | Manual                          |
| <b>DRIVE SYSTEM</b>       |                                 |
| Drive type                | Friction Disk                   |
| Number of gears           | 6 Fwd / 2 Rev                   |
| Tire size                 | 13" x 5" (33 x 13 cm)           |
| Thread                    | Arctic Trac™                    |
| <b>HANDLES / CONTROLS</b> |                                 |
| Free Hand Control™        | Standard                        |
| Headlight                 | Standard                        |
| Heated hand grips         | n/a                             |
| <b>ACCESSORIES</b>        |                                 |
| Drift cutters             | n/a                             |
| Storage cover             | n/a                             |
| Snow cab                  | n/a                             |

## BM924E Dual Stage - Medium Duty Snow Blower



- 24" (61 cm) Clearing Width
- Briggs & Stratton 900 Snow Series™ Engines
- Electric Start
- Notched Steel Auger
- Electric 200° Chute Rotation
- Remote Deflector
- Free Hand™ Control
- Rugged Artic Trac™ Tires
- Halogen Headlights
- Reversible Skid Shoes

## Specifications

|                           |                                    |
|---------------------------|------------------------------------|
| Stage                     | Dual Stage - Medium Duty           |
| <b>AUGER / IMPELLER</b>   |                                    |
| Clearing width            | 24" (61 cm)                        |
| Intake height             | 19.5" (50 cm)                      |
| Auger style               | Steel - Notched                    |
| Auger diameter            | 12" (30 cm)                        |
| Impeller diameter         | 12" (30 cm)                        |
| Impeller style            | 3 Blades                           |
| <b>ENGINE</b>             |                                    |
| Engine displacement       | 205 cc                             |
| Engine type               | 4-Cycle - OHV                      |
| Starting system           | Recoil Start + 230V Electric Start |
| Oil                       | 0W30 Synthetic                     |
| <b>CHUTE</b>              |                                    |
| Chute style               | Steel                              |
| Chute rotation            | 200° Electric                      |
| Chute deflector           | Remote                             |
| <b>DRIVE SYSTEM</b>       |                                    |
| Drive type                | Friction Disk                      |
| Number of gears           | 6 Fwd / 2 Rev                      |
| Tire size                 | 15" x 5" (38 x 13 cm)              |
| Thread                    | Arctic Trac™                       |
| <b>HANDLES / CONTROLS</b> |                                    |
| Free Hand Control™        | Standard                           |
| Headlight                 | Standard                           |
| Heated hand grips         | n/a                                |
| <b>ACCESSORIES</b>        |                                    |
| Drift cutters             | Optional                           |
| Storage cover             | Optional                           |
| Snow cab                  | Optional                           |

## BM1227SE Dual Stage - Medium Duty Snow Blower



- 27"(69 cm) Clearing Width
- Briggs & Stratton 1150 Snow Series™ Engines
- Electric Start
- Notched Steel Auger
- Electric 200° Chute Rotation
- Remote Deflector
- Free Hand™ Control
- Cast Iron Gear Box
- Rugged Artic Trac™ Tires
- Halogen Headlights
- Reversible Skid Shoes



## Specifications

|                           |                                    |
|---------------------------|------------------------------------|
| Stage                     | Dual Stage - Medium Duty           |
| <b>AUGER / IMPELLER</b>   |                                    |
| Clearing width            | 27" (69 cm)                        |
| Intake height             | 21" (53 cm)                        |
| Auger style               | Steel - Notched                    |
| Auger diameter            | 12" (30 cm)                        |
| Impeller diameter         | 12" (30 cm)                        |
| Impeller style            | 3 Blades                           |
| <b>ENGINE</b>             |                                    |
| Engine displacement       | 250 cc                             |
| Engine type               | 4-Cycle - OHV                      |
| Starting system           | Recoil Start + 230V Electric Start |
| Oil                       | 0W30 Synthetic                     |
| <b>CHUTE</b>              |                                    |
| Chute style               | Steel                              |
| Chute rotation            | 200° Electric                      |
| Chute deflector           | Remote                             |
| <b>DRIVE SYSTEM</b>       |                                    |
| Drive type                | Transmission                       |
| Number of gears           | 6 Fwd / 2 Rev                      |
| Tire size                 | 16" x 4.8" (41 x 12 cm)            |
| Thread                    | Arctic Trac™                       |
| <b>HANDLES / CONTROLS</b> |                                    |
| Free Hand Control™        | Standard                           |
| Headlight                 | Standard                           |
| Heated hand grips         | Standard                           |
| <b>ACCESSORIES</b>        |                                    |
| Drift cutters             | Optional                           |
| Storage cover             | Optional                           |
| Snow cab                  | Optional                           |

## BH1730SE Dual Stage - Heavy Duty Snow Blower



- 30" (76 cm) Clearing Width
- Briggs & Stratton 1650 Professional Series™ Engines
- Electric Start
- Serrated Steel Auger
- Electric 200° Chute Rotation
- Electric Deflector
- Free Hand™ Control
- Cast Iron Gear Box
- Rugged Artic Trac™ Tires
- Halogen Headlights
- Heated Hand Grips
- Reversible Skid Shoes

## Specifications

|                           |                                    |
|---------------------------|------------------------------------|
| Stage                     | Dual Stage - Heavy Duty            |
| <b>AUGER / IMPELLER</b>   |                                    |
| Clearing width            | 30" (76 cm)                        |
| Intake height             | 21" (53 cm)                        |
| Auger style               | Steel - Serrated                   |
| Auger diameter            | 14" (36 cm)                        |
| Impeller diameter         | 12" (30 cm)                        |
| Impeller style            | 3 Blades                           |
| <b>ENGINE</b>             |                                    |
| Engine displacement       | 342 cc                             |
| Engine type               | 4-Cycle - OHV                      |
| Starting system           | Recoil Start + 230V Electric Start |
| Oil                       | 0W30 Synthetic                     |
| <b>CHUTE</b>              |                                    |
| Chute style               | Steel                              |
| Chute rotation            | 200° Electric                      |
| Chute deflector           | Electric                           |
| <b>DRIVE SYSTEM</b>       |                                    |
| Drive type                | Transmission                       |
| Number of gears           | 6 Fwd / 2 Rev                      |
| Tire size                 | 16" x 6.5" (41 x 17 cm)            |
| Thread                    | Arctic Trac™                       |
| <b>HANDLES / CONTROLS</b> |                                    |
| Free Hand Control™        | Standard                           |
| Headlight                 | Standard                           |
| Heated hand grips         | Yes, with On/Off switch            |
| <b>ACCESSORIES</b>        |                                    |
| Drift cutters             | Optional                           |
| Storage cover             | Optional                           |
| Snow cab                  | Optional                           |

## BP2132SE Dual Stage - Pro Duty Snow Blower



- 32" (81 cm) Clearing Width
- Briggs & Stratton 2100 Professional Series™ Engines
- Electric Start
- Serrated Steel Auger
- Electric 200° Chute Rotation
- Electric Deflector
- Free Hand™ Control
- Professional Easy Turn™ Transmission
- Cast Iron Gear Box
- Rugged Artic Trac™ Tires
- Halogen Headlights
- Heated Hand Grips
- Reversible Skid Shoes

## Specifications

|                           |                                    |
|---------------------------|------------------------------------|
| Stage                     | Dual Stage - Pro Duty              |
| <b>AUGER / IMPELLER</b>   |                                    |
| Clearing width            | 32" (81 cm)                        |
| Intake height             | 19.75" (51 cm)                     |
| Auger style               | Steel - Serrated                   |
| Auger diameter            | 14" (36 cm)                        |
| Impeller diameter         | 12" (30 cm)                        |
| Impeller style            | 4 Blades                           |
| <b>ENGINE</b>             |                                    |
| Engine displacement       | 420 cc                             |
| Engine type               | 4-Cycle - OHV                      |
| Starting system           | Recoil Start + 230V Electric Start |
| Oil                       | 0W30 Synthetic                     |
| <b>CHUTE</b>              |                                    |
| Chute style               | Steel                              |
| Chute rotation            | 200° Electric                      |
| Chute deflector           | Electric                           |
| <b>DRIVE SYSTEM</b>       |                                    |
| Drive type                | Professional Easy Turn™            |
| Number of gears           | 6 Fwd / 2 Rev                      |
| Tire size                 | 16" x 6.5" (41 x 17 cm)            |
| Thread                    | Arctic Trac™                       |
| <b>HANDLES / CONTROLS</b> |                                    |
| Free Hand Control™        | Standard                           |
| Headlight                 | Standard                           |
| Heated hand grips         | Yes, with On/Off switch            |
| <b>ACCESSORIES</b>        |                                    |
| Drift cutters             | Optional                           |
| Storage cover             | Optional                           |
| Snow cab                  | Optional                           |



**По вопросам продаж и поддержки обращайтесь:**

Архангельск (8182)63-90-72,  
Астана+7(7172)727-132,  
Белгород(4722)40-23-64,  
Брянск(4832)59-03-52,  
Владивосток(423)249-28-31,  
Волгоград(844)278-03-48,  
Вологда(8172)26-41-59,  
Воронеж(473)204-51-73,  
Екатеринбург(343)384-55-89,  
Иваново(4932)77-34-06,  
Ижевск(3412)26-03-58,  
Казань(843)206-01-48,  
Калининград(4012)72-03-81,  
Калуга(4842)92-23-67,  
Кемерово(3842)65-04-62,  
Киров(8332)68-02-04,

Краснодар(861)203-40-90,  
Красноярск(391)204-63-61,  
Курск(4712)77-13-04,  
Липецк(4742)52-20-81,  
Магнитогорск(3519)55-03-13,  
Москва(495)268-04-70,  
Мурманск(8152)59-64-93,  
Набережные Челны(8552)20-53-41,  
Нижний Новгород(831)429-08-12,  
Новокузнецк(3843)20-46-81,  
Новосибирск(383)227-86-73,  
Орел(4862)44-53-42,  
Оренбург(3532)37-68-04,  
Пенза(8412)22-31-16,  
Пермь(342)205-81-47,  
Ростов-на-Дону(863)308-18-15,

Рязань(4912)46-61-64,  
Самара(846)206-03-16,  
Санкт-Петербург(812)309-46-40,  
Саратов(845)249-38-78,  
Смоленск(4812)29-41-54,  
Сочи(862)225-72-31,  
Ставрополь(8652)20-65-13,  
Тверь(4822)63-31-35,  
Томск(3822)98-41-53,  
Тула(4872)74-02-29,  
Тюмень(3452)66-21-18,  
Ульяновск(8422)24-23-59,  
Уфа(347)229-48-12,  
Челябинск(351)202-03-61,  
Череповец(8202)49-02-64,  
Ярославль(4852)69-52-93